

ELECTRODELESS INDUCTION LAMPS



Induction Lamp Specifications:

Product No.	Model No.	Wattage (W)	Operating Frequency (KHz)	Rated Initial Luminance (Lm)	Efficacy (Lm/W)	Luminance Maintenance (60 Khrs)	CRI	Color Temperature (K)	Average Lifetime (hrs)	
B40SDCW	BS40	40	250	2600-2800	65-70	70%	≥80	4000	100,000	
B40SDWW								5000		
B70SDCW	BS70	70		4900-5250	70-75			4000		5000
B70SDWW										
B80SDCW	BS80	80		5600-6000	70-75			4000		5000
B80SDWW										
B100SDCW	BS100	100		7600-8000	75-80			4000		5000
B100SDWW										
B120SDCW	BS120	120		9000-9600	75-80			4000		5000
B120SDWW										
B150SDCW	BS150	150		11250-12000	75-80			4000		5000
B150SDWW										
B200SDCW	BS200	200		16000-17000	80-85			4000		5000
B200SDWW										
B250SDCW	BS250	250		20000-21250	80-85			4000		5000
B250SDWW										
B300SBCW	BS300	300	25500-27000	85-90	4000	5000				
B300SBWW							4000			
B400SDCW	BS400	400	34000-36000	85-90	4000	5000				
B400SDWW							4000			

- Ⓜ Note: 1. Color Temperature 2720-6500 available upon request.
 2. Operating ambient temperature 0°C ~ +50°C (without fixture, or with open fixture).
 3. Operating ambient temperature -20°C ~ +50°C (with enclosed fixture).
 4. Product for operating at ambient temperature (-40°C ~ 0°C) available upon request.