

ELECTRODELESS INDUCTION LAMPS



Induction Lamp Specifications:

Product No.	Model No.	Wattage (W)	Operating Frequency (KHz)	Rated Initial Luminance (lm)	Efficacy (lm/W)	Luminance Maintenance (40 Khrs)	CRI	Color Temperature (K)	Average Lifetime (hrs)
B40RCW	BR40	40	250	2600-2800	65-70	70%	≥ 80	4000	100,000
B40RWW								5000	
B70RCW	BR70	70		4900-5250	70-75			4000	
B70RWW									
B80RCW	BR80	80		5600-6000	70-75			4000	
B80RWW									
B100RCW	BR100	100		7500-8000	75-80			4000	
B100RWW									
B120RCW	BR120	120		9000-9600	75-80			4000	
B120RWW									
B150RCW	BR150	150		11250-12000	75-80			4000	
B150RWW									
B200RCW	BR200	200	16000-17000	80-85	4000				
B200RWW						5000			
B250RCW	BR250	250	21250-22500	85-90	4000				
B250RWW						5000			
B300RCW	BR300	300	25500-27000	85-90	4000				
B300RWW						5000			

- ※ Note: 1. Color Temperature 2720-6500 available upon request.
 2. Operating ambient temperature 0°C - +50°C (without fixture, or with open fixture).
 3. Operating ambient temperature -20°C - 50°C (with enclosed fixture).
 4. Product for operating at ambient temperature (-40°C - 0°C) available upon request.