

Compact Induction Bulb that's Self-Ballasted
40Watt 120V/208V/240V/277V

Saves Energy!
Long Life!

**THIS BULB MAY QUALIFY FOR A REBATE
FROM YOUR ENERGY PROVIDER!**

Compact Induction Bulb

Self-ballasted 120V / 277VAC Medium Base
Energy Saving Bulb for use in Commercial Recessed Cans,
Low Bays and most other Conventional Light fixtures



Outlasts Conventional bulbs Approx. 3.5 years average life
Outshines Conventional bulbs 80+ CRI - Colors Crisp & Brilliant
Creates Less Heat Than Conventional Bulbs

Compare 40 Watt brightness:
120W+HPS bulb*, 120W+Mercury Vapor*,
200W+Incandescent,
80W+ Metal halide**

*Based on (21CRI) **Based on (65CRI)

B4026RCW	Cool White	5000k	120V-277V
B4026RWW	Soft White	3000k	120V-277V

Uses: Shopping Centers, Theatres, Office,
Parking Garages, Warehouses,
Commercial Cans, Eaves,



NOTE: - MILLER SELF-BALLASTED INDUCTION BULBS DO NOT REQUIRE AN ADDITIONAL BALLAST
Do Not Put " Compact Induction bulb" in HID fixtures without consulting with an electricalian first
to remove existing ballasts and for re-wiring fixture or socket when and if necessary.

Specifications:

Wattage: 40 Watts 2800 Lumens

CRI \geq 80

Voltage: 120/208/240/277 V AC

AMPS :0.36/0.21/0.18/0.15

Base : (E26) Medium

Soft White 3000k



Cool White 5000k

Efficacy (Lm/W) 65-70

Frequency: 50-60 HZ

Power Factor: \geq 0.95

Average lifetime (hrs)30,000



USA & CANADA

1-800-445-6611

FAX 1-800-445-6690

MILLER
ecolighting products

PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

www.MillerLightingProducts.com

Customerservice@millerlightingproducts.com