

## FLUORESCENT SOCKETS

## Medium Bi-Pin Butt-On

- A. L395W (white)  
B. L395-2W (white) with two 4-32 trapped holes


660W-600V, (2) 1/8" dia. mounting holes, rapid-start lampholder with 6" leads



## Single Pin Slimline

- A. L466 - (660W-1000V)  
B. L467 - (660W-600V)

Dim. 2-21/64"Ht. x 1-29/64" W



## Snap-In Quickwire Slimline

- A. L516  
B. L517

suggested panel opening 1.520", 660W-600V

Shallow Base Slide On  
(660W-1000V)

- A. L2537  
B. L2536

designed for 20ga. panel mount

Slide-On Self-Aligning for  
U-Shape Lamps


- L13180-U (standard)

660W-600V, 18-20ga. panel mount

Safety Tube Locks  
white plastic reusable

## T199

locks fluorescent Bi-Pin, Tubes in place for added safety and longer tube life

Medium Bi-Pin for  
U-Shape Lamps

- L13180 (standard)

660W-600V, Dim. 1-1/8" Ht. x 1-3/16" W

Medium Bi-Pin Shunted  
For Electronic Ballasts

## L23351

low profile 18 & 20 ga., 660W-600V



## Circline Connector

four leads (black, white, blue, red)

## L408

660W-600V

Medium Bi-Pin  
L3901W

Dim. 1-55/64" Ht x 1-7/16" W,  
flush or suurface mounting  
660W-600V



## Medium Bi-Pin


- A. L13351-U -18 & 20 ga. panel  
B. L13051UN - 20 ga. with nut  
C. L13053UN - 18 ga. with nut

low profile, 660W-600V, Dim. 1-43/64", Ht. x 1-11/64" W.

Miniature Bi-Pin for T5 Lamp  
75W-250V

- A. L420

- B. L420B  
(bracket)



## Medium Bi-Pin Standard


- A. L13357-U -18 ga. panel  
B. L13357-UN - captive nut  
C. L13355-U - 20 ga. panel mount

660W-600V, Dim. 2-33/64",  
Ht. x 1-3/8" W.

Miniature Bi-Pin Snap-In  
Quickwire

- A. L13518 - (spring loaded)  
B. L13519 - (fixed end)

suggested panel opening 1.520", 660W-600V



USA & CANADA

1-800-445-6611

FAX: 1-800-445-6690

WWW.MillerLightingProducts.com

**MILLER**  
ecoLIGHTING PRODUCTS

PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

Customerservice@MillerLightingProducts.com