

ELECTRONIC CFL BALLASTS

**CFL Ballast for (1 or 2)
13, 18 or 26 watt lamps
MRAD131826**

Features: 120V ac only - Class P 50/60 Hz.
Rapid start Type 1 outdoor UL/cUL listed
Starting temp. 0°F. End of life protection.
Mounting holes 4.5



L- 5", W- 2.4", H- .8"

**Single Lamp Mini Ballast for 13 & 26 watt
Electronic Preheat (Rapid start) Normal Power Factor**

A. MR00113-13 watt

CFQ13W/G24q, CFTR13W/GX24q,
F13T5 or F8T5

B. MR00126-26 watt

CFQ26W/G24q, CFTR26W/GX24q,
CFS28W/GR10q or F32T8, F25T8, F15T8,
F13T8, F18T8, F19T8

Class P-Type 1 Outdoor Inherent thermal
protection 120V ac 50/60 Hz UL & cUL Listed



L- 4", H- 1-1/4", W- 1-7/8"

MILLER RACEHORSE
UNIVERSAL VOLTAGE
ELECTRONIC BALLAST
MODEL NO. MRAD131826
CFQ-13W-13
FOR USE IN CONTACT WITH
CFL, CFL-R, CFL-RO, CFL-RO-2, CFL-RO-3, CFL-RO-4, CFL-RO-5, CFL-RO-6, CFL-RO-7, CFL-RO-8, CFL-RO-9, CFL-RO-10, CFL-RO-11, CFL-RO-12, CFL-RO-13, CFL-RO-14, CFL-RO-15, CFL-RO-16, CFL-RO-17, CFL-RO-18, CFL-RO-19, CFL-RO-20, CFL-RO-21, CFL-RO-22, CFL-RO-23, CFL-RO-24, CFL-RO-25, CFL-RO-26, CFL-RO-27, CFL-RO-28, CFL-RO-29, CFL-RO-30, CFL-RO-31, CFL-RO-32, CFL-RO-33, CFL-RO-34, CFL-RO-35, CFL-RO-36, CFL-RO-37, CFL-RO-38, CFL-RO-39, CFL-RO-40, CFL-RO-41, CFL-RO-42, CFL-RO-43, CFL-RO-44, CFL-RO-45, CFL-RO-46, CFL-RO-47, CFL-RO-48, CFL-RO-49, CFL-RO-50, CFL-RO-51, CFL-RO-52, CFL-RO-53, CFL-RO-54, CFL-RO-55, CFL-RO-56, CFL-RO-57, CFL-RO-58, CFL-RO-59, CFL-RO-60, CFL-RO-61, CFL-RO-62, CFL-RO-63, CFL-RO-64, CFL-RO-65, CFL-RO-66, CFL-RO-67, CFL-RO-68, CFL-RO-69, CFL-RO-70, CFL-RO-71, CFL-RO-72, CFL-RO-73, CFL-RO-74, CFL-RO-75, CFL-RO-76, CFL-RO-77, CFL-RO-78, CFL-RO-79, CFL-RO-80, CFL-RO-81, CFL-RO-82, CFL-RO-83, CFL-RO-84, CFL-RO-85, CFL-RO-86, CFL-RO-87, CFL-RO-88, CFL-RO-89, CFL-RO-90, CFL-RO-91, CFL-RO-92, CFL-RO-93, CFL-RO-94, CFL-RO-95, CFL-RO-96, CFL-RO-97, CFL-RO-98, CFL-RO-99, CFL-RO-100

Model Number	Operates Lamps
MBRH1	1 or 2 x QD13, 1 or 2 x TR13, 1 or 2 x TW7, TW9, TW11, 1 or 2 x ZD10, 1 x ZD16
MBRH2	1 or 2 x QD18, 1 or 2 x TR18, 2 x ZD16, 1 or 2 x ZD21
MBRH3	1 or 2 x QD26, 1 or 2 x TR26, 1 x TR32, TR42, 1 x T5CR22, T5CR40, 1 or 2 x TW13, 2 x TW24/27, 2 x ZD21, 1 x ZD26, ZD36

TW - Twin
TR - Triple
QD - Quad
DC - Double Quad
F - Fluorescent
FP - Flat Quad
TP - Twin 15mm
DQ - Quad 15mm
TZ, T5, T6, T8 - Quad Dimmed

L- 4-7/8", H- 1-1/4", W- 2-3/8"

Frequency 50-60 Hz.
Min. temp. -20°F (30°C)
Program preheat start
Class P (thermal)

FEATURES:
120 to 277 volts
High power factor
End-of life protection
Operates 1 or 2 lamps
Twin, triple, quad, double quad
9- 70 watts
UL, cUL, CE listed
Type 1 outdoor

Smart Sensor Electronic Ballast

120V to 277V AC 50/60 Hz.

**MQSHB26 - 26, 32, 42W PLT/C
6-1/2" x 2-7/8" x 1-1/8"**

1 or 2 lamp functions, Auto Reset, Plug
in connectors, UL listed/ cUL Certified,
Class P thermally protected, End of
lamp life protection circuit



Soft start, programmed start,
flicker free, up to 25% energy
savings, surge protector, four
pin lamp applications.

MAGNETIC CFL & CIRCLINE BALLASTS

Combo Magnetic Ballast

UL & CSA Listed

BH132 -13W with 12" leads



Clamp Core

120V AC
single lamp
normal power factor

L-3-1/16" H-1-3/4" D-1-15/32"

A. B254 - 7-9W B. B255 -13W



Open Core & Coil

120V AC
single lamp
normal power factor
L-2-3/4" H-1-5/8" D-1-1/4"

A. B252 - 7-9W B. B253 -13W



Electronic Circline Ballasts

A. BAC22 - 22W

B. BAC32 - 32W



C. BAC3222

32W & 22W Combo Ballast
FC8T9/FC12T9



USA & CANADA

1-800-445-6611

FAX WATS 1-800-445-6690

www.MillerLightingProducts.com



PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

customerservice@millerlightingproducts.com