

FLUORESCENT SOCKETS (shunted)
(Specially designed for use with Electronic Ballasts)

Medium Bi-Pin standard size
660W-600V

A. L23355 - 18 ga. panel
B. L23357 - 20 ga. panel
1 1/32" thick



T5 Bi-Pin Energy Efficient

A. L13336C - With Clip
B. L13336NC - No Clip



Snap-in low profile rotary lock medium base lampholder
LA200-10 1-1/2" tall

instant start, accomodates panel thickness from 22 up to 18ga/rated 660W-600V,



T5 Bi-Pin Energy Efficient (shunted)

A. L23336C With Clip
B. L23336NC - No Clip



Medium Bi-Pin straight-in
L23150-UR7

low profile 18 & 20 ga., 660W-600V




Rear View of L136666C-L23666C with Clip



FLUORESCENT SOCKETS (HO & VHO's)
(Specially designed for use with Electronic Ballasts)

High Output Rapid Start
silver plated recessed contacts, Dim. 2-21/64" x 1-29/64", 660W-600V, horizontal contacts, 800&1500MA T12

A. L464 **B. L465**




High Output Pedestal Type
slide-on shallow base, 660W-600V, 800&1500MA, 20ga. panel mount, horizontal contacts

A. L13550 **B. L13551**



High Output Slide-On Shallow Base
Dim. 2-29/64" Ht. x 1 7/16"W., 660W-600V, vertical contacts, 800&1500MA, 20ga. panel mount

A. L13556 **B. L13557**



Snap-In Quickwire Lampholder
suggested panel opening 1.520", 660W-600V, 800&1500MA

A. L523 **B. L524**



Medium Bi-Pin High Output
silver plated contacts slide-on, shallow base 660W-600V, 20ga. panel mount

A. L13570 **B. L13571**



High Output Lampholder
Dim. 2-21/64" Ht. x 1-29/64"W., 660W-600V, 800&1500MA

A. L492 **B. L493** (vertical contacts)
C. L488 **D. L489** (horizontal contacts)



USA & CANADA
1-800-445-6611
FAX: 1-800-445-6690



PHOENIX, AZ
Phone: 602-268-0001
Fax: 602-268-0130

www.MillerLightingProducts.com

customerservice@millerlightingproducts.com