

BAYONET & SPECIAL SOCKETS

Halogen G8 Socket & Bulbs

250V-100W

- A. G8F4
- B. G8F6



GU10 Socket

- A. GU10PH (1/8 IP hickey)
 - B. GU10P (bottom leads)
- 6" high temp leads, 100W-250V



**Halogen R7S Socket
LWR7S**

200° wire, 500W-250V, Nickel plated brass with 6" leads



Flange Mounting Halogen

- A. L554 - FRONT FLANGE
- B. L555 - REAR FLANGE

200° wire, 3000W-600V with 18" leads



**Porcelain Body
LDA005**

UL, 1000W-250V, G4.0 / G5.3 / G6.35 with 6" leads



**Quartz Bayonet Sockets
Double Contact**


- A. L910-200 - Mounting Bracket
 - B. L910-001 - 1/8 IPS Male Bushing
- 18 ga.200° wire, 500W-125V with 9" leads



Metal Halide Lamps with G12 Base

L557 porcelain lampholder is designed for single-ended metal halide lamps with a G12 base, rated up to 150 watts. Standard leads (2) are White, No. 18 AWG SEW-2 200°C 600V wire, 12" long, stripped 1/2".

Ideal for indoor accent and display lighting, including gallery, museum and showroom applications



L557

660W-600V 5KV PULSE RATED

Single & Double Contacts

- A. L905 - Single Lead
- B. L905B - Double Lead
- C. L905-2 - Double Contact

Low Voltage Applications with 9" leads



High Pressure Sodium Lamps with PG-12 Base

L558 porcelain lampholder is designed for high-pressure sodium lamps with a PG-12 base, such as the Philips SDWT-T 35-50- and 100-watt White Son lamps. Standard leads, one Red (pulse) and one Blue, are No. 18 AWG SEW-2 200°C 600V wire, 12" long, stripped 1/2"

These lamps provide excellent brightness and color rendition for galleries, museums, showrooms and other accent and display light applications.



L558

660W-600V 5KV PULSE RATED

G9 Socket & Barrel

- A. LB258301
- B. LB259303

rear push wire contacts, screw or snap-in mount, 1/8 IP threaded barrel, ceramic socket



USA & CANADA

1-800-445-6611

FAX: 1-800-445-6690

www.MillerLightingProducts.com



PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

customerservice@millerlightingproducts.com