

INCANDESCENT PORCELAIN (Medium)

Side Mount with Leads

- A. L10092FL (porcelain) **V+**
 - B. L10092FLB (bakelite nipple 1")
- 1/8 IPS nipple 1-3/8, 660W-250V
9" 105 C°. leads. with ground wire



Twin Lampholder

- A. L4010F **V+**
 - B. L4010FL **V+** (9" lds.)
 - C. L4010FL-15 **V+** (15" lds.)
- Bushing 1/8 IPS, 660W-250V



Twin Sockets

- A. L4005F **V+**
- 1/8 IPS Bushing, 660W-250V
- B. L4008F **V+**
- 1/8 IPS Double Bushing,
660W-250V



A. B.

One Piece

(For Recessed Units)

L9885

mounting hole 1 3/8" c-c with
8-32 tap bushings



Two Hole Flange

(With Shadeholder Groove)

L9878

2 mounting holes 2" c-c
660W-600V



Surface Mounted

L326T

2 mounting holes 2" c-c,
height 1 19/32 C°,
660W-250V, 6"- 105°. lds.



Phenolic Flanged Adapter

660W-250V **V+**

- A. L165(10" leads) B. L3152-F (6" leads)



**Lampholder & Adapter Harness
Comination**

L1551T

660W-200V, 18ga. 150 C°. - 10" long



Hanging Cordset

MW8403

SVT 18/3 cord 10 feet 250V 660W
Available in Black and White



Two-Piece

L9350

660W-250V



Two-Piece Ring Type

L8101

660W-250V, 18 ga. 9" long



One-Piece Snap-In

L8885

660W-250V



Heavy Duty Lampholder

L30F

V+

660W-250V



Angle Pan Socket

L18315

660W-250V



**Two-Piece
Condensed Terminal**

L9880F

V+

aluminum shell, 660W-250V



One-Piece Shallow Shoulder

- A. L8880 (standard)
- B. L8881
- C. L8881-9 (9" leads)

24" leads, 660W-250V,
hole size 1-7/16"



**Medium Base Par
Connector**

L368

for par 46 & 38, porcelain
body, 660W-250V



**Medium Base to MR16
Halogen Adapter**

LALP42245

10" 18ga SF-1 200°C
leads, brass screw shell



One-Piece Snap-On

- A. L8875 **VALUE PLUS**
- B. L8875F **PLUS**
- C. L8876 (9" leads)

mounting hole 1 13/32, 660W-250V



USA & CANADA

1-800-445-6611

FAX: 1-800-445-6690

www.MillerLightingProducts.com



PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

customerservice@millerlightingproducts.com