

INCANDESCENT PORCELAIN (Medium)

Straight Body

- A. L10045-8 (domestic)
 - B. L10045-8F **VALUE PLUS**
 - C. L10045-4 1/4 IPS cap **VALUE PLUS**
- 1/8 IPS cap, 660W-250V
(cap and washer included)



Side Outlet 660W-250V

- A. L10091F **VALUE PLUS**
 - B. L10091FL **V+** - 9" - 150 C° leads)
 - C. L10091-L15 **V+** - 15" leads)
- 2-1/4" length / 1/8" IPS Bushing



Straight Body with Leads

- A. L10045-8FL **VALUE PLUS**
9" - 150 C° lds.
 - B. L10045-824FL **VALUE PLUS**
24" - 150 C° lds.
- 1/8 IPS cap, 660W-250V
(cap and washer included)



**Single Circuit 1/8IPS Hickey
660W-250V**

- A. L3152-8 (domestic)
- B. L3152-8F **VALUE PLUS**



**Single Circuit Screw Hole
Mounting**

- A. L8052-830 (center hole)
 - B. L8052-999 (mounting hole)
- 9" - 105 C° leads 660W-250V



Keyless 660W-250V

- A. L10085 (domestic)
- B. L10085F **VALUE PLUS**
with 6 - 32 screws
- A. L10085-5 (domestic)
- B. L10085-5F **V+**
with 6 - 32 bushings



Single Circuit 1/8IP Hickey

- A. L8052-8 (domestic)
 - B. L8052-8F **VALUE PLUS**
- 9" - 105dg. leads 660W-250V



3-Wire Grounding 660W-250V

- A. L10088-8 (domestic)
 - B. L10088-8F **VALUE PLUS**
 - C. L10088-8FL (with leads) **V+**
 - D. L10088-8FL (domestic)
- (green grounding screw cap and washer included)



Bracket

- L3152-F **V+**
- 660W-250V



Snap-In

- L8064F **V+**
- 9" - 105dg. leads



Threaded Single Circuit

- A. L20070F **VALUE PLUS**
 - B. L9395 (METAL RING ONLY)
- cap and metal ring included
660W-250V



A.

B.

Caps and Washers (Die-cast for medium base)

- A. L3347-8 1/8 IPS
- B. L3347-8F 1/8 IPS
- C. L3347-4 1/4 IPS
- D. L1916-2 1/2 IPS



USA & CANADA

1-800-445-6611

FAX: 1-800-445-6690

www.MillerLightingProducts.com



PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

customerservice@millerlightingproducts.com