

## WIRES & CORDSETS

**High Temperature Wire Connector**  
(Switch 24" from Socket 105°C)

### WP3B

UL listed, 100 Pcs per pack only,  
300V / 150°C, #22-#14 awg, Max.2  
#16 / Min.3 #22, Black



### Screw-On Wire Connectors

(Spring Inserts) UL listed

- W71 - gray
  - A. W72 - blue
  - B. W73 - orng.
  - D. W74 - yel.
  - E. W76 - red
  - C. W80 - yel. wing nut
- bulk pack only minimum 100 pcs.



### Porcelain Connectors

(high heat applications)

- A. W77-P - 2-4 #18
- B. W78-P - 2-5 #18
- C. W79-P - 2-4 #16



### "Snap-In" Bushing

(hole size: 7/16)

- A. W90 - black
- B. W91 - white
- C. W90-6 - black



### Plastic Pipe Hole Bushing

Fits into pipe to protect against  
Wire Cuts

- A. W28 - 1/8 IPS
- B. W28-4 - 1/4 IPS



### Strain Relief

for SPT - 1 hole 7/16"

- A. W53 - black
- B. W54 - white



### Insulated Strain Relief

### W75



### Metal Strain Relief

### W96

use with SVT or SJT cord



### SVT Strain Reliefs

- A. A3B - black
- B. A3W - white



### SVT Strain Reliefs

### A7B - black



### SVT Strain Reliefs

- A. A6B - black
- B. A6W - white
- C. A5B -black (inquire)



### Bakelite Bushings

(Male)

- A. W84 - white (1/8 IPS)
- B. W85 - black (1/8 IPS)
- C. W88 - white (1/4 IPS)
- D. W89 - black (1/4 IPS)

(Female)

- A. W82 - white (1/8 IPS)
- B. W83 - black (1/8 IPS)
- C. W86 - white (1/4 IPS)
- D. W87 - black (1/4 IPS)

(Male)



(Female)



### Easy Push-In Wire Nuts

UL & CSA approved

- A. WW162 - yellow 2-conductor
- B. WW112- green 2-conductor
- C. WW164- orange 4-conductor
- D. WW114- green 4-conductor
- E. WW124- white 4-conductor
- F. WW166- purple 6-conductor
- G. WW116- green 6-conductor
- H. WW168- grey 8-conductor
- I. WW118- green 8-conductor

All take: 12-16 AWG stranded copper  
(stranding pattern less than or equal to 19)  
12-18 AWG solid copper

600V building wiring, 1000V fixtures & signs,  
20A maximum, 150°C rated (221°F)

Clear housing allows visual confirmation  
of connection. Test port for easy continuity  
testing



### 3 Conductor Spring Pressure Clamp Connector

### WW22

3-Conductor with  
Levers, Cross  
Section: 3 x 28-12  
AWG Solid or Stranded,  
600V/20A, Color: gray,  
Subpack: 50



Easy as  
1, 2, 3



USA & CANADA  
1-800-445-6611  
FAX: 1-800-445-6690

**MILLER**  
eco LIGHTING PRODUCTS

PHOENIX, AZ  
Phone: 602-268-0001  
Fax: 602-268-0130