

LED Flexible Strips

Energy Saving Products

Connectable / Waterproof IP67

12 Volts

Premium Grade 3M adhesive backing

Connect up to 32.80' per run (using proper Driver)

Latest LED technology for optimal performance and energy saving



HOME

AUTO

BOATS

MFLXSTRP6SW

6" L x 7/16" W x 1/8" H Soft White LED Flex Strip 59 lm

MFLXSTRP6C

6" L x 7/16" W x 1/8" H Cool White LED Flex Strip 64 lm

6"

6" lead wires on both ends to connect multiple strips
3M adhesive backing for mounting
0.73 watts approx. energy consumption
1 strip per package -



Connection Directions

Connect strips together at lead-ends following the proper continuity. Splicing leads together using butt-connectors and / or (shrink tubing). See maximum runs lengths. Follow allfederal & local codes.

MFLXSTRP12SW

12" L x 7/16" W x 1/8" H Soft White LED Flex Strip 119 lm

MFLXSTRP12C

12" L x 7/16" W x 1/8" H Cool White LED Flex Strip 128 lm

12"

6" lead wires on both ends to connect multiple strips
3M adhesive backing for mounting
1.46 watts approx. energy consumption
1 strip per package -



MFLXSTRP39SW

39.37" L x 7/16" W x 1/8" Soft White LED Flex Strip 390 lm

MFLXSTRP39C

39.37" L x 7/16" W x 1/8" Cool White LED Flex Strip 420 lm

39"

6" lead wires on both ends to connect multiple strips
3M adhesive backing for mounting
4.80 watts approx. energy consumption
1 strip per package -



LED DRIVERS

Recommended for use from 120V AC to 12V DC

MVB-12030M

#MVB-12060P



{ USE Only for up to 19.68' = 28.80W}

{Use Only for up to 39.37' (32.80' per run) = 57.60W}

30Watt 12 V DC WaterProof LED Driver IP66 rated
Input: 90V-130V AC, 50/60Hz, Output: 12V DC, DC2.5A
8-9/16" L x 1-3/16" W x 13/16" H (mount tabs 8-1/8"ctr)
Aluminum Housing - Lead length 7.5"

60Watt 12 V DC Waterproof LED Driver IP66
Input: 90V-130VAC, 50/60Hz, Out: 12VDC, DC5A
7" L x 2-3/4" W x 2-1/8" H (mount tabs 6-1/2"ctr)
Aluminum Housing - Lead Length 11.5"

USA & CANADA

Phone: 800-445-6611

Fax: 800-445-6690

www.MillerLightingProducts.com



PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

Customerservice@MillerLightingProducts.com