

LED Rope Lighting

Uses 0.8 watts per foot

Energy Smart

1/2" 150' Reel

2-wire LED Rope

UL



Warm White
(LEDR-SW)



Cool White
(LEDR-CW)

FEATURES

- * Cost effective lighting for a variety of applications
- * Vibrant, long lasting colors that grab attention
- * Produces virtually no heat for maximum safety
- * Bulk reels can be field cut (no longer UL Listed if reel is cut and/ or spliced) for maximum project flexibility.
- * Bulk reels include one pre-attached power cord, five "Connection Kits" and fifty mounting clips.
- * Sold in 150 feet reels only

TECHNICAL SPECIFICATIONS

- Voltage: 120V, 60Hz AC operation (1.6A inverter converts AC to DC)
- Construction: Heat resistant clear PVC housing with LEDs every 1.2", horizontal mount
- Mounting: Use clear plastic clips or track
- Dimensions: 1/2" diameter
- Cuttability: Every 36"
- Wattage: 0.8 watt per foot
- Maximum run: 150 feet
- Switching: Customer must provide switched outlet for On/Off and dimming Control
- Linking: Cutting, Splicing or repairing custom cuts voids the UL2388 rating
- Packaging: Miller Lighting Products Logo on white carton.
- LED Specs: 60,000 hours average LED life (WH & WW); 100,000 hours average life for all other colors.
- Dimmers: Dimmable with most standard incandescent, low voltage magnetic, low voltage electronic dimmers.
- Warranty: 2 Year Warranty

Notes: Do not operate Rope Light while coiled on reel.
In any outdoor installation, all conductors must be coated with dielectric grease, and properly sealed with silicone and shrink tube.



ACCENT LIGHTING COVE LIGHTING DECORATIVE LIGHTING
BUILDING OUTLINES ARCHITECTURAL DETAILS
BOOKSHELVES PATIOS, DECKS & GAZEBOS

ACCESSORIES

LEDR-CKIT

Non-UL power connector kit with five foot cord, power connector and endcap; 1.6A inverter on cord, Two prong polarized plug.



LEDR-CLIP

Clear U-shaped mounting clip with screws, securely holds 1/2" 2 wire LED RopeLight.



LEDR-CON

Non-UL splice connector, includes power pin connector.



LEDR-TR

Four foot clear mounting track with UV rating for outdoors; recommended for use with straight line installations.



LEDR-CAP

Non-UL End cap for 2 wire LED RopeLight



USA & CANADA
Phone: 800-445-6611
Fax: 800-445-6690

MILLER
ecoLIGHTING PRODUCTS
www.MillerLightingProducts.com

PHOENIX, AZ
Phone: 602-268-0001
Fax: 602-268-0130